

Teflon ET 22553 PTFE Coated Glass Tape

- Self-adhesive
- Easy to apply
- Burn-resistant
- Does not stick to weld material
- Available in 1m multiples
- Special rates available for a 30 metre roll

Technical Specification

ET 22553 is manufactured from a 6 thou or 0.152mm standard grade PTFE impregnated fibreglass with 0.05mm of high temperature silicone pressure sensitive adhesive. This product is almost chemically inert. Only molten alkali metals and fluorine under elevated temperatures and pressure will attack the PTFE surface. The fibreglass provides dimensional stability

and restricts PTFE cold flow. The PTFE surface provides a quick-release surface ideal for PVC-u weld heads.

Physical Properties (Physical properties are typical values and should not be used for writing specifications)

Adhesion	45oz/in. width
Break strength	120 lbs/in. width
Elongation	<5 %
Backing thickness	0.152mm
Adhesive thickness	0.05mm
Temperature range	-75 to +260°C
Insulation class	180°C

Finish	Type	Part Code	Box Qty.
Brown	Premium Self Adhesive	TEF10000	1m ²
Brown	Non Adhesive	TEF20000	1m ²
Green	Non Adhesive	TEF20001	1m ²
Green	Self Adhesive	TEF10001	1m ²
Red	Self Adhesive	TEF10003	1m ²
Silver	Self Adhesive	TEF10002	1m ²

